

Protimeter TimberMaster

Advanced Moisture Meter specifically designed for the timber industry

Protimeter TimberMaster is an advanced moisture meter specifically designed for the timber industry. It is ideal for a range of quality control applications associated with moisture levels within all wood products.

Features and Benefits

- Simple hand-held design
- Durable and rugged
- Built in wood calibration scales - 150 wood species
- Large LCD for ease of use in all conditions
- Hammer electrode for sub-surface measurements (optional)
- Automatic temperature correction with temperature sensor (optional)



When precise wood moisture measurements are required, there is no substitute for the **Protimeter TimberMaster**

TimberMaster Specifications

Measure 150 Wood Species

The Protimeter TimberMaster features eight calibration scales, enabling the user to take accurate moisture measurements in 150 wood species from around the world.

Simple Operation

Moisture measurements are commonly taken using the integral pin electrodes. The appropriate wood calibration scale can be selected to ensure the accurate measurements are taken.

Temperature Compensation

If the timber being measured is significantly above or below 20 degree C (70 degree F) the Protimeter TimberMaster should be used in conjunction with the optional temperature probe. When the probe is connected to the instrument the measured moisture value is automatically corrected for the effect of temperature.

Hammer Electrode

A slide-hammer electrode can be used with the Protimeter TimberMaster to measure sub-surface moisture levels (to a depth of 30mm/1 $\frac{3}{16}$ ") irrespective of surface moisture levels.

Operating Conditions:

- Operating temperature range: 0°C to 50°C
- Humidity: 0 to 90% RH, non-condensing

Measurement Specifications:

Moisture measurement:

- Pin measurement range (% MC in wood)
- 7.9 to 99% (readings over 30% are relative)

Physical Specifications:

Power:

- 9V- Alkaline 550mAh, Battery low indication on LCD

Size:

- 19cm x 6.5cm x 3.5cm (7.5" x 2.5" x 1.4")

Gross Weight (without battery):

- ~228g

Maximum Needle Depth:

- For WME pins: 0.4" (10mm)

Buzzer:

- Audible buzzer for key tone and measurement indication, user configurable

Regulatory Compliance:

- CE, RoHS, ETL

Part Numbers:

- BLD5605 – Supplied with Heavy Duty moisture probe and temperature probe
- BLD5609 – Supplied with Heavy Duty moisture probe

Warranty:

- 2 years



Light Duty Hammer Electrode - BLD5000



Heavy Duty Hammer Electrode - BLD5055



Heavy Duty Moisture Probe - BLD5060

Amphenol
Advanced Sensors

www.protimeter.com

www.amphenol-sensors.com

© 2021 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.

AAS-920-679B - 12/2021